



Features	Spider	Spider Duo
<b>10/100 Ethernet</b>	•	•
<b>2nd Cascade Ethernet Port</b>	•	
<b>RS232 Port</b>	•	•
<b>USB Port (VIP Access bootstrap)</b>		•
<b>Remote Access (Up to 8 simultaneous connections)</b>	•	•
<b>Local Access</b>		•
<b>Video: HD15VGA</b>	•	•
<b>Compatible with DVI-A or DVI-I adapter</b>	•	•
<b>Keyboard/Mouse: USB</b>	•	•
<b>Keyboard/Mouse: PS2</b>	•	•
<b>Server Powered</b>	•	
<b>External Power Supply</b>	Optional, 5VDC @ 1A	Included, 5VDC @ 2A
<b>Cables Included</b>	•	•
<b>Standard Length Cables</b>	21"	21.6"
<b>Extended Length Cables</b>	58"	59"
<b>Resolution (*hardware rev G22+,E21+ )</b>	1600x1200*,1280x1024, 1024x768 800x600	1600x1200, 1280x1024, 1024x768, 800x600
<b>IPv6 Ready</b>	Firmware 3.0+	•
<b>Browser Driven. Requires No Special Software Installation</b>	•	•
<b>Virtual Media</b>	•	•
<b>BIOS Level Access</b>	•	•
<b>Generate and Send Wake-On-LAN Packet</b>	Firmware 3.0+	•
<b>VIP Access</b>	Firmware 2.2+	•
<b>Power Control Unit Compatible</b>		•
<b>Telnet/SSH</b>	•	•
<b>HTTP/HTTPS</b>	•	•
<b>Local User/Group Authentication</b>	•	•
<b>Remote Authentication: LDAP, RADIUS, Active Directory</b>	•	•
<b>OS System Supported</b>	Win 98/2000/2003/XP/Vista, Unix, Linux, MAC OSX 10	Win 2000/2003/2008/XP/Vista, Unix, Linux, MAC OSX 10
<b>RoHS</b>	•	•
<b>Environmental Operating Temp</b>	0° to 45° C (32° to 115° F)	0° to 45° C (32° to 115° F)
<b>Environmental Storage Temp</b>	-20° to 70° C (-4° to 158° F)	-20° to 70° C (-4° to 158° F)
<b>Dimensions</b>	13.2 x 5.8 x 3.1 cm (5.2 x 2.3 x 1.2 in)	13.2 x 5.8 x 3.6 cm (5.2 x 2.3 x 1.4 in)
<b>Weight w/cables</b>	185g (6.6 oz)	USB: 269g (9.50 oz) PS/2: 278g (9.80 oz)
<b>Warranty</b>	2 YR	2 YR

**Lantronix Corporate Headquarters**  
167 Technology Drive  
Irvine CA 92618  
t: 800.422.7055  
[sales@lantronix.com](mailto:sales@lantronix.com)

**European Headquarters**  
t: +31 (0) 76 52 36 74 4  
[EMEA@lantronix.com](mailto:EMEA@lantronix.com)

**Asia/Pacific Headquarters**  
t: +852 3428 2338  
[asiapacific\\_sales@lantronix.com](mailto:asiapacific_sales@lantronix.com)

**Japan Headquarters**  
t: +81.3.6277.8802  
[japan\\_sales@lantronix.com](mailto:japan_sales@lantronix.com)